

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 December 2005 (29.12.2005)

PCT

(10) International Publication Number
WO 2005/124082 A1

(51) International Patent Classification⁷: **E05F 15/10**,
E06B 3/48

(21) International Application Number:
PCT/KR2005/000999

(22) International Filing Date: 7 April 2005 (07.04.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10-2004-0024164 8 April 2004 (08.04.2004) KR

(71) Applicant and

(72) Inventor: LEE, Wan Young [KR/KR]; 103-202 Gwanak
Hyeondae Apt., 1000 Bongcheon 3-dong, Gwanak-gu,
Seoul 151-755 (KR).

(74) Agent: CHOI, Jong Won; 4th Fl. Ssangma Bldg., 828-23
Yeoksam-dong, Gangnam-gu, Seoul 135-935 (KR).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KM, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,
ZM, ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: FOLDING AND SPREADING SYSTEM FOR HALF SPREAD FOLDING DOOR



(57) Abstract: A folding and spreading system for a half spread folding comprises an upper (11) and a lower (15) guider for making the folding door (D) move in a close or open direction; a first wire guider (21) provided at the depth portion of each door leaf (P) in a predetermined distance from a neighboring first wire guider (21), and a second wire guider (22) installed coaxially to the first wire guider (21); a folding motor (31) and a spreading motor (33) provided at both end frames (F2, F3) of the folding door (D), respectively, and having a reel (32, 34) at each rotational shaft of each motor (31, 33); and a winding wire (41) and a releasing wire (42) extended diagonally through each of the wire guiders (21, 22) of each door leaf (P), respective end of the wires (41, 42) connected to the wire guider and to the reel (32, 34) of the motor (31, 33), respectively, in order to fold and spread the adjacent two door leaves (P) around the hinge (H).